# CAPTIONS (H" x W")

FAIR-PLAY

| HOME<br>Visitor<br>Inning | 12" x 45"<br>12" x 52"<br>12" x 37" |
|---------------------------|-------------------------------------|
| BALL                      | 12" x 51"                           |
| STRIKE                    | 12" x 30"                           |
| OUT                       | 7" x 4"                             |
| Н                         | 7" x 5"                             |
| E                         | 7" x 26"                            |

## DIGIT SIZES (H")

| BALL          | 18" |
|---------------|-----|
| OUT           | 18" |
| STRIKE        | 18" |
| INNING SCORES | 15" |
| TOTAL         | 15" |
|               |     |

# MODEL: BA-7120-2



Length

20'-0"

| D | IM | E | ٧S | <b>IO</b> | NS |
|---|----|---|----|-----------|----|
|   |    |   |    |           |    |

Height 6'-6"

Depth Weight

436 lbs.

### STANDARD EQUIPMENT

- Super-bright, wide-angle amber LED's
- 4-level control console display brightness adjustment
- 5-year limited warranty
- Easy access built-in service points
- Quality engineered water resistant aluminum
- Complete, secure and durable display mounting
- Built-in lightning suppressor (for standard data • direct wire only)
- Request a free project design renderings ٠
- Help Desk Support
- USA Factory authorized national and local sales, service and installation

#### **OPTIONAL EQUIPMENT**

10"

- Full-color electronic message displays
- Integrated scoring and display systems ٠
- Illuminated, non-illuminated identification ٠ and sponsorship signage
- · Personalized vinyl home team name
- Scoreboard caption color (other than white)
- Custom, unique signage options
- Scoreboard control carrying case
- Truss and decorative steel systems
- Power lighting protector •

## ELECTRICAL

### **OPERATING TEMPERATURES**

| Voltage | Hertz | Watts | AMPS | Phase | Wiring          | Circuits<br>Required | Safety<br>Listing | Scoreboard Display |               | Control Console |                           |
|---------|-------|-------|------|-------|-----------------|----------------------|-------------------|--------------------|---------------|-----------------|---------------------------|
| 120 VAC | 60    | 340   | 3    | 1     | 2-Wire + ground | 1                    | ETL/CETL          | -22° to 131° F     | -30° to 55° C | 32° to 131° F   | $0^\circ$ to $55^\circ$ C |

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

#### For applicable models, consult with a sales representative on the following:

- · Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names ٠
- ٠ Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions electronic available, operated via control
- Pitch Speed or Pitch Count Display Systems

Please see Color Chart PDF for all scoreboard color options.

UV resistant custom paint & vinyl trim colors available.