

# CAPTIONS (H" x W")

| HOME    | 12" x 45" |
|---------|-----------|
| VISITOR | 12" x 52" |
| INNING  | 12" x 37" |
| BALL    | 12" x 51" |
| STRIKE  | 12" x 30" |
| OUT     | 7" x 4"   |
| Н       | 7" x 5"   |
| E       | 7" x 26"  |

## DIGIT SIZES (H")

| BALL          | 18" |
|---------------|-----|
| OUT           | 18" |
| STRIKE        | 18" |
| INNING SCORES | 15" |
| TOTAL         | 15" |

## MODEL: BA-7120



| DIMENSIONS | Height | Length | Depth | Weight   |
|------------|--------|--------|-------|----------|
|            | 6'-6"  | 20'-0" | 10"   | 436 lbs. |

#### STANDARD EQUIPMENT

- Super-bright, wide-angle amber LED's
- 4-level control console display brightness adjustment
- 5-year limited warranty
- Easy access built-in service points
- Quality engineered water resistant aluminum
- Complete, secure and durable display mounting
- Built-in lightning suppressor (for standard data direct wire only)
- Request a free project design rendering
- Help Desk Support
- USA Factory authorized national and local sales, service and installation

### **OPTIONAL EQUIPMENT**

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification and sponsorship signage
- · Personalized vinyl home team name
- Scoreboard caption color (other than white)
- · Custom, unique signage options
- · Scoreboard control carrying case
- Truss and decorative steel systems
- Power lightning protector

Please see Color Chart PDF for all scoreboard color options.

UV resistant custom paint & vinyl trim colors available.

### **ELECTRICAL**

| Voltage | Hertz | Watts | AMPS | Phase | Wiring          | Circuits<br>Required |          |
|---------|-------|-------|------|-------|-----------------|----------------------|----------|
| 120 VAC | 60    | 340   | 3    | 1     | 2-Wire + ground | 1                    | ETL/CETL |

| Scoreboard Disp | lay           | Control Console |             |  |
|-----------------|---------------|-----------------|-------------|--|
| -22° to 131° F  | -30° to 55° C | 32° to 131° F   | 0° to 55° C |  |

**OPERATING TEMPERATURES** 

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

#### For applicable models, consult with a sales representative on the following:

- Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names
- Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions electronic available, operated via control
- Pitch Speed or Pitch Count Display Systems