

18"


CAPTIONS (H")

Colon Diameter 3"

DIGIT SIZES (H")

Pitch Timer

MODEL: PT-052418-06-2



STANDARD EQUIPMENT

- Super-bright, wide-angle amber LED design
- For additional cost specify on order if standard color other than black is requested
- 4-level control console display brightness adjustment
- 5-year limited warranty
- Easy access built-in service points
- Complete, secure and durable mounting
- Built-in lightning suppressor (for standard data direct wire only)
- Request a free project design rendering
- Help Desk Support

ELECTRICAL

USA Factory authorized national and local sales, service and installation

OPTIONAL EQUIPMENT

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification and sponsorship signage
- Custom, unique signage options
- Scoreboard control carrying case
- Truss and decorative steel systems
- Power lightning protector or protective net

Please see Color Chart PDF for all scoreboard color options.

UV resistant custom paint & vinyl trim colors available.

OPERATING TEMPERATURES

Voltage	Hertz	Watts	AMPS	Phase	Wiring	Circuits Required	Safety Listing	Scoreboard Display		Control Console	
120 VAC	60	70	2	1	2-Wire + ground	1	ETL/CETL	-22° to 131° F	-30° to 55° C	32° to 131° F	0° to 55° C

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

For applicable models, consult with a sales representative on the following:

- Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names
- Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions electronic available, operated via control
- Integrated, second operator statistics control

FAIRPLAY CORPORATION 800.247.0265 • fair-play.com Nearly a Century of Scoring Experience 6110 Aviator Drive, Hazelwood, M0 63042