

# CAPTIONS (H" x W")

HOME	6" x 18"
VISITOR	6" x 25"
PERIOD	4" x 16"
BONUS	4" x 15"
POSS	3" x 9"
FOULS (Personal)	4" x 14"
FOULS (Team)	4" x 14"
PLAYER	4" x 17"
TIMEOUTS	4" x 23"
LEFT	4" x 11"
NO	4" x 6"
F	4" x 2"
PTS	4" x 8"
Colon Diameter	1.5"

### DIGIT SIZES (H")

Game Clock	12"
Team Scores	12"
Period	10"
Team Fouls	10"
Player Number	10"
Personal Fouls	10"
Timeouts Left	10"
Stats Fouls	6"
Stats Player	6"
Stats Points	6"

# MODEL: CST-1600-10



DIMENSIONS	Height	Length	Depth	Weight
	39 9/16"	9'-5 3/8" without end pads 9'-10 3/8" with end pads	39 5/16" with 18" folding table top	480 lbs.

#### STANDARD EQUIPMENT

- Energy efficient LED designs
- Three distinct LED digit colors to visually organize critical game information
- Heavy-duty, vibrating horn (103 dB)
- 4-level control console display brightness adjustment
- 5-year limited warranty
- Easy access built-in service points
- Quality engineered water resistant aluminum
- Complete, secure and durable display mounting
- Built-in lighting suppressor (for standard data direct wire only)
- Request a free project design renderings
- Help Desk Support
- USA Factory authorized national and local sales, service and installation

#### **OPTIONAL EQUIPMENT**

- Full-color electronic message displays
- Integrated scoring and display systems
- Illuminated, non-illuminated identification and sponsorship signage
- Personalized vinyl home team name
- Scoreboard caption color (other than white)
- Custom, unique signage options
- Scoreboard control carrying case
- Truss and decorative steel systems
- Power lighting protector or protective net
- Count side tables options in 8ft,10ft or 7.7ft long configured with front BB scoreboard
- Synchronized locker room game / time of day clocks

Please see Color Chart PDF for all scoreboard color options. UV resistant custom paint &

vinyl trim colors available.

## **ELECTRICAL**

## **OPERATING TEMPERATURES**

120 VAC 60 02 12 1 2 Wire Largund 1 ETL/CETL 200 to 1210 E 200 to 1210 E 00 to 1	Vo	oltage	Hertz	Watts	AMPS	Phase	Wiring	Circuits Required	Safety Listing	Scoreboard Disp	lay	Control Console	
120 VAC   00   92   12   1   2-Wile + glouid   1   E1D/6E1E   -22 (0.131 F   -30 (0.55 C   32 (0.131 F   0.05	12	20 VAC	60	92	12	1	2-Wire + ground	1	ETL/CETL	-22° to 131° F	-30° to 55° C	32° to 131° F	0° to 55° C

All weights and measures are approximate. To confirm specifications please contact your local Fair-Play representative.

### For applicable models, consult with a sales representative on the following:

- · Choice of Fair-Play's scorekeeper approved score systems
- Electronic Team Names
- Rear-illuminated scoreboard captions or scoreboard sport-conversion captions (electronic)
- Changeable scoreboard game captions electronic available, operated via control
- Integrated, second operator statistics control